

Package: ChauBoxplot (via r-universe)

May 21, 2026

Type Package

Title Chauvenet-Type Boxplot

Version 1.0.0

Description Provides a modified boxplot with a new fence coefficient determined by Lin et al. (2025). The traditional fence coefficient $k=1.5$ in Tukey's boxplot is replaced by a coefficient based on Chauvenet's criterion, as described in their formula (9). The new boxplot can be implemented in 'base R' with function `chau_boxplot()`, and in 'ggplot2' with function `geom_chau_boxplot()`.

Maintainer Tiejun Tong <tongt@hkbu.edu.hk>

URL <https://tiejuntong.github.io/ChauBoxplot/>

License GPL-3

Encoding UTF-8

RoxygenNote 7.3.2

Imports ggplot2, stats

Depends R (>= 4.0.0)

Suggests testthat (>= 3.0.0)

Config/testthat/edition 3

Repository <https://tiejuntong.r-universe.dev>

Date/Publication 2026-02-19 13:26:27 UTC

RemoteUrl <https://github.com/tiejuntong/chauboxplot>

RemoteRef HEAD

RemoteSha 9f1b66cc3074b2153319f677f6d4092a24abaaf5

Contents

ChauBoxplot-package	2
chau_boxplot	2
geom_chau_boxplot	3

Index	5
--------------	----------

ChauBoxplot-package *ChauBoxplot: Chauvenet-type boxplot*

Description

This package provides a modified boxplot with the new fence coefficient determined by Lin et al. (2025). Specifically, the fence coefficient $k=1.5$ in Tukey's boxplot has been replaced by the fence coefficient associated with Chauvenet's criterion in their formula (9). For convenience, we have also provided the chauvenet-type boxplot in both base R with function `chau_boxplot()`, and in `ggplot2` with function `geom_chau_boxplot()`.

Author(s)

Maintainer: Tiejun Tong <tongt@hkbu.edu.hk>

Authors:

- Hongmei Lin <hmlin@suibe.edu.cn>
- Riquan Zhang <rqzhang@suibe.edu.cn>

References

Hongmei Lin, Riquan Zhang and Tiejun Tong (2025). When Tukey meets Chauvenet: a new boxplot criterion for outlier detection. *Journal of Computational and Graphical Statistics*, accepted.

See Also

Useful links:

- <https://tiejuntong.github.io/ChauBoxplot/>

chau_boxplot *Title: Chauvenet-type boxplot in base R*

Description

This function can be operated the same way as `boxplot()` in base R, except that the fence coefficient $k=1.5$ in Tukey's boxplot is replaced by the fence coefficient associated with Chauvenet's criterion. For details, please refer to formula (9) in Lin et al. (2025).

Usage

```
chau_boxplot(data, group_col = NULL, value_col = NULL, ...)
```

Arguments

data	The data frame containing the data.
group_col	The column name for grouping data.
value_col	The column name for the values to plot.
...	Additional arguments passed to the plotting function.

Value

A Chauvenet-type boxplot in base R.

References

Hongmei Lin, Riquan Zhang and Tiejun Tong (2025). When Tukey meets Chauvenet: a new boxplot criterion for outlier detection. *Journal of Computational and Graphical Statistics*, accepted.

Examples

```
# Example 1
chau_boxplot(c(rnorm(1000),5,6))

# Example 2
rate.senior <- c(4.96, 6.30, -5.38, 1.60, 7.24, 5.26, 2.55, 5.96, 3.96,
                4.19, 1.88, 4.06, 4.75, 0, 0, 2.5, 2.87, 3.00)/100
chau_boxplot(rate.senior, notch=TRUE)
```

geom_chau_boxplot *Title: Chauvenet-type boxplot in ggplot2*

Description

This function can be operated the same way as `geom_boxplot()` in `ggplot2`, except that the fence coefficient $k=1.5$ in Tukey's boxplot is replaced by the fence coefficient associated with Chauvenet's criterion. For details, please refer to formula (9) in Lin et al. (2025).

Usage

```
geom_chau_boxplot(
  mapping = NULL,
  data = NULL,
  geom = "boxplot",
  position = "dodge2",
  na.rm = FALSE,
  show.legend = NA,
  inherit.aes = TRUE,
  ...
)
```

Arguments

mapping	Aesthetic mappings created by 'aes()'.
data	The data to be displayed in this layer.
geom	The geometric object to use for display.
position	The position adjustment.
na.rm	Logical. Should missing values be removed?
show.legend	Logical. Should this layer be included in the legends?
inherit.aes	If FALSE, overrides the default aesthetics.
...	Other arguments passed to the layer.

Value

A ggplot2 layer with the Chauvenet-type boxplot.

References

Hongmei Lin, Riquan Zhang and Tiejun Tong (2025). When Tukey meets Chauvenet: a new boxplot criterion for outlier detection. *Journal of Computational and Graphical Statistics*, accepted.

Examples

```
# Example 1
library(ggplot2)

rate.senior <- c(4.96, 6.30, -5.38, 1.60, 7.24, 5.26, 2.55, 5.96, 3.96,
                4.19, 1.88, 4.06, 4.75, 0, 0, 2.5, 2.87, 3.00)/100
year <- 2007:2024
data.senior <- data.frame(x=year, y=rate.senior)

C.boxplot.senior <-
  ggplot(data.senior, aes(y=rate.senior)) +
  geom_chau_boxplot(fill="purple",width=3) +
  theme(legend.position = "none") +
  scale_x_discrete(breaks = NULL) +
  ylim(-0.057,0.077) +
  theme(plot.margin = unit(c(0, 0, 0, 0), "inches")) +
  labs(title="C.boxplot", subtitle="Senior civil servants", x="", y="")

print(C.boxplot.senior)
```

Index

`chau_boxplot`, [2](#)
`ChauBoxplot` (`ChauBoxplot-package`), [2](#)
`ChauBoxplot-package`, [2](#)
`geom_chau_boxplot`, [3](#)